



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61M 1/16, A61K 33/14	A1	(11) International Publication Number: WO 00/44418 (43) International Publication Date: 3 August 2000 (03.08.00)
(21) International Application Number: PCT/EP00/00130 (22) International Filing Date: 7 January 2000 (07.01.00) (30) Priority Data: MI99A000176 29 January 1999 (29.01.99) IT (71) Applicant (for all designated States except US): BIEFFE MEDITAL, S.P.A. [IT/IT]; Via Nuovo Provinciale, Grosotto 23034, Sondrio (IT). (72) Inventors; and (75) Inventors/Applicants (for US only): MAZZA, Mario [IT/IT]; Via Besta, 12, I-23037 Tirano (IT). PESCI, Giampiero [IT/IT]; Via Vecchio Molino, 3, I-23037 Tirano (IT). (74) Agent: DEE, Ian; Eric Potter Clarkson, Park View House, 58 the Ropewalk, Nottingham NG1 5DD (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: CARTRIDGE FOR DIALYSIS CONTAINING SODIUM BICARBONATE		
(57) Abstract <p>A cartridge (10) is provided containing sodium bicarbonate in solid form. The cartridge (10) is usable in a haemodialysis machine for continuously producing a buffer solution, which is mixed with another solution to produce a dialysis solution. The cartridge (10) also contains a solid acid or acid anhydride, or carbon dioxide gas. This has been found to overcome problems caused by a temporary high pH in the dialysis solution during the early stages of a dialysis operation.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

CARTRIDGE FOR DIALYSIS CONTAINING SODIUM BICARBONATE

5 This invention relates to dialysis cartridges containing solid sodium bicarbonate.

BACKGROUND

 It has long been known to use cartridges containing drugs, or other
10 substances, in solid form and to pass water or a solution through the cartridge to dissolve the solid substance continuously, e.g. for continuous administration to a patient.

 Examples are WO-A-86/03417 and US-A-4432756.

 It is also known, as disclosed in EP-A-0278100 to provide sodium
15 bicarbonate in solid form for use as a buffer in haemodialysis. Sodium bicarbonate is stored separately from the rest of a dialysis solution, which contains calcium and magnesium ions, to prevent calcium and magnesium carbonate precipitation. A cartridge of sodium bicarbonate powder is inserted in a haemodialysis machine and water is passed through the
20 cartridge. The powder is gradually dissolved, so that a solution of sodium bicarbonate is continuously produced. The solution is continuously flowed through the machine, mixing with the rest of the dialysis solution in-line upstream of the dialyzer. There is, therefore, only a short dwell time in the machine after mixing, so that the problem of calcium and
25 magnesium carbonates being precipitated is avoided.

 A problem does, however, arise with such cartridges. The pH of the mixed dialysis solution is monitored upstream of the dialyzer. If the pH falls outside a given range, then an alarm is triggered. It has been found that this often happens during the first twenty minutes of flow,
30 when the machine is being set up for operation. After this period, no

2

problems are encountered. This causes substantial inconvenience to personnel operating haemodialysis machines, since the problem has to be investigated and the machine reset, each time the alarm is triggered.

5 The inventors have discovered that the problem is probably caused by contamination of the sodium bicarbonate powder with a small amount of sodium carbonate. The bicarbonate is less soluble than the carbonate, so that a high pH is caused by the dissolution of the carbonate in the early stages. Once the carbonate has dissolved, the problem disappears. It is,
10 however, difficult and expensive to produce a sodium bicarbonate powder, which is not contaminated with sodium carbonate.

A possible solution to the problem once it was realised that sodium carbonate precipitation was the cause, would be to introduce a further line
15 upstream of the pH monitoring device to add dilute acid solution to the dialysis solution during the first twenty minutes of use of the cartridge. This could be done upstream or downstream of the cartridge. This involves, however, modification of the dialysis solution, use of an additional solution and additional operational control.

20

The inventors have found that the problem can be relatively simply solved by modifying the contents of the cartridge.

SUMMARY OF THE INVENTION

25 The present invention relates to a cartridge having an openable sealed inlet and an openable sealed outlet, for connection in-line in a haemodialysis machine for passage of water, or a solution through the cartridge, the cartridge containing sodium bicarbonate in solid form.

In accordance with the invention, the cartridge additionally contains an acid, or acid anhydride in solid form, or carbon dioxide gas.

When the cartridge is mounted in a haemodialysis machine and
5 water is passed through the cartridge, the acid or acid anhydride (including carbon dioxide) is gradually dissolved, decreasing the pH of the resulting solution to counteract any temporary increase in pH caused by sodium carbonate contamination.

10 The amount of acid or acid anhydride provided is preferably predetermined, so that it is leached from the cartridge during the initial 10 to 30 minutes, i.e. during the period that sodium carbonate is also likely to be leached from the cartridge.

15 Carbon dioxide may be added to the cartridge, during manufacture, in solid form, i.e. as dry ice, prior to sealing the cartridge.

Acids which may be used in solid form may be organic acids, e.g. citric acid, or tartaric acid, citric acid being preferred for clinical
20 acceptability.

The cartridge may contain at least 0.2g of acid, or acid anhydride per 1000g of sodium bicarbonate; preferably at least 0.5g per 1000g and most preferably at least 1g per 1000g. The preferred embodiment
25 contains 2.7g per 1000g.

DRAWINGS

The invention is described with reference to the accompanying drawings, wherein:-

4

Fig 1. is a side elevation of a cartridge according to the invention, shown partly in cross-section; and

Fig 2. is a diagrammatic illustration of the cartridge of fig 1 connected in a haemodialysis machine.

5

PREFERRED EMBODIMENTS

The currently preferred embodiments of the invention are now described. The construction of haemodialysis machines is well known, as is the construction of a sodium bicarbonate cartridge for use in a haemodialysis machine. The machine and the cartridge are not, therefore, described in detail. The cartridge may be of the type sold under the trademark EASYCART by Bieffe Medital S.p.A. of Italy.

The cartridge 10 comprises a body 14, closed by a lid 15 and defining a chamber 11. The body and lid are injection moulded in polypropylene. The chamber 11 contains sodium bicarbonate in granular, crystalline form, although other solid forms are possible. The lid 15 is sealed to the body 14 by ultrasonic welding. The lid 15 has an inlet 12 and the body had an outlet 13, both sealed closed in the as-moulded state, by integral membranes 17, 18 respectively.

The cartridge 10 is connected in-line in a first line 20 for receiving deionised water at 21 and supplying sodium bicarbonate solution to a main line 22, at 23. The membranes 17, 18 are perforated during clamping of the cartridge into the machine, by piercing means provided on the machine. The main line 22 also receives deionised water at 24. A container 30, containing a solution of the other ingredients of a dialysis solution, is connected to the main line 22 by a second line 25 at 26. A final dialysis solution is formed at point 26 and the main line 22 feeds this

5

to a dialyzer 40. A pH detector 50 is connected to the main line 22 downstream of point 26 and upstream of the dialyzer. The detector is connected with a control system (not shown), which produces an alarm, if a pH outside a predetermined range is exceeded. This range is usually 6.8 to 7.9 pH may be monitored by other means, such as by conductivity measurement.

The solution in the container 30 may contain any of the components usually provided in a dialysis solution, such as calcium and magnesium chloride, sodium chloride and an osmotic agent, such as dextrose.

In accordance with the present invention, the cartridge contains, in addition to the sodium bicarbonate, an acid or acid anhydride in solid form, or carbon dioxide gas, so as to avoid any sodium carbonate contamination causing a temporary increase in the pH of the dialysis solution to a degree sufficient to exceed the predetermined threshold and trigger an alarm.

The preferred embodiment of a cartridge contains 750g sodium bicarbonate and 2g citric acid, both in granular, crystalline form. A similar weight ratio could be used with different amounts of sodium bicarbonate.

Alternatives to citric acid are preferably provided in the same weight ratio.

Tests were carried out using cartridges containing 750g sodium bicarbonate and citric acid, tartaric acid, or carbon dioxide (added as dry

6

ice) respectively. These were compared with similar cartridges, to which no acid or carbon dioxide had been added.

The tests were carried out by running an Integra (trademark) haemodialysis machine, using the various cartridges. Notes were made of which cartridges produced an alarm signal, due to the pH of the mixed dialysis solution falling outside the predetermined range. The actual maximum pH of each solution was also recorded. "Acid" solutions, ie the solutions carrying the other components of the dialysis solution, were standard solutions produced by Gambro. In each case, the pH of the water supplied was 6.1. The results are shown in the tables below. There were numerous false alarms with the reference cartridges, but no false alarms with the cartridges according to the invention.

15 Table 1

This shows the results using the reference cartridges, containing 750g sodium bicarbonate and no added acid or carbon dioxide.

Sample No.	Maximum pH of dialysis solution	Alarm Yes/No
1	7.9	No
2	7.8	No
3	8	Yes
4	8.1	Yes
5	7.9	No
6	8	Yes
7	8.2	Yes
8	8	Yes
9	7.4	No
10	7.4	No

Table 2

This shows the results using cartridges according to the invention, containing 2g citric acid and 750g sodium bicarbonate.

5

Sample No.	Maximum pH of dialysis solution	Alarm Yes/No
11	7.5	No
12	7.5	No
13	7.5	No
14	7.5	No
15	7.4	No
16	7.4	No
17	7.4	No
18	7.4	No
19	7.4	No
20	7.4	No
21	7.4	No

Table 3

10 This shows the results using cartridges according to the invention, containing 0.5g or 1g of carbon dioxide (dry ice) and 750g sodium bicarbonate.

Sample No.	Amount of CO ₂ (g)	Maximum pH of dialysis solution	Alarm Yes/No
22	0.5	7.5	No
23	1.0	7.3	No
24	0.5	7.5	No
25	1.0	7.3	No
26	1.0	7.3	No

Table 4

This shows the results using cartridges according to the invention, containing 1g tartaric acid and 750g sodium bicarbonate.

5

Sample No.	Maxiumum pH of dialysis solution	Alarm Yes/No
27	7.5	No
28	7.5	No

Other tests were carried out using different "acid" solutions, and water of different pH. In each case, a cartridge according to the invention did not cause any alarm due to either high or low pH.

10

CLAIMS


1. A cartridge having an openable, sealed inlet and an openable, sealed outlet, for connection in-line in a haemodialysis machine for
5 passage of water, or a solution through the cartridge, the cartridge containing sodium bicarbonate in solid form,
characterised in that the cartridge additionally contains an acid, or acid anhydride in solid form, or carbon dioxide gas.
- 10 2. A cartridge according to Claim 1, wherein the acid is in powder form.
3. A cartridge according to Claim 1 or 2, wherein the acid is citric acid.
- 15 4. A cartridge according to Claim 1 or 2, wherein the acid is tartaric acid, or another organic acid.
5. A cartridge according to any preceding claim containing at least
20 0.2g of acid, acid anhydride, or carbon dioxide per 1000g of sodium bicarbonate.
6. A cartridge according to Claim 5, wherein the cartridge contains at least 0.5g of acid, acid anhydride, or carbon dioxide per 1000g of sodium
25 bicarbonate.
7. A method of preventing a temporary increase of pH in a dialysis solution being continuously produced in a haemodialysis machine from different component sources including a cartridge containing solid sodium

10

bicarbonate, the method comprising including in the cartridge an acid or acid anhydride in solid form, or carbon dioxide gas.

8. A method according to Claim 7, wherein the cartridge and its
5 contents are in accordance with any one of Claims 1 to 6.

9. A method of introducing carbon dioxide gas to a cartridge according to Claim 1, wherein the carbon dioxide is introduced as dry ice.






Fig. 2

INTERNATIONAL SEARCH REPORT

Inter. Application No
PCT/EP 00/00130

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61M1/16 A61K33/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61M A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 92 11046 A (UNIV WASHINGTON) 9 July 1992 (1992-07-09) page 2, line 36 -page 4, line 9; figure 2	1-8
X	EP 0 177 614 A (TOMITA PHARMA) 16 April 1986 (1986-04-16) page 4, paragraph 1 -page 5, paragraph 1	1-8
X	EP 0 417 478 A (NIKKISO CO LTD ;TOWA PHARMACEUTICAL CO LTD (JP)) 20 March 1991 (1991-03-20) page 2, line 1 -page 3, line 22	1-8
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

11 April 2000

Date of mailing of the international search report

26/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Zeinstra, H

INTERNATIONAL SEARCH REPORT

Inter Application No
PCT/EP 00/00130

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DATABASE WPI Section Ch, Week 199118 Derwent Publications Ltd., London, GB; Class B05, AN 1991-128481 XP002135441 & JP 03 066621 A (NIKKISO CO LTD), 22 March 1991 (1991-03-22) abstract -----	1-8
X	WO 94 25084 A (BAXTER INT) 10 November 1994 (1994-11-10) page 6, line 4 - line 25 -----	1-8
A	WO 97 02056 A (ALTHIN MEDICAL AB ;CARLSSON PER OLOV (SE); GILLERFALK BJOERN (SE);) 23 January 1997 (1997-01-23) page 1, line 5 - line 18 page 4, line 14 - line 29; figure 1 -----	1,7,9

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 00/00130

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9211046	A	09-07-1992	CA 2098839 A AU 7171091 A DE 69027052 D DE 69027052 T DK 567452 T EP 0567452 A GR 3020698 T HK 1007969 A JP 6503233 T	19-06-1992 22-07-1992 20-06-1996 26-09-1996 14-10-1996 03-11-1993 31-10-1996 30-04-1999 14-04-1994
EP 0177614	A	16-04-1986	WO 8503435 A US 4655941 A	15-08-1985 07-04-1987
EP 0417478	A	20-03-1991	JP 3275626 A JP 2986810 B JP 3074331 A DE 69018172 D DE 69018172 T US 5071558 A	06-12-1991 06-12-1999 28-03-1991 04-05-1995 09-11-1995 10-12-1991
JP 3066621	A	22-03-1991	JP 2739898 B	15-04-1998
WO 9425084	A	10-11-1994	US 5383324 A AT 161426 T AU 683878 B AU 6447394 A CA 2138665 A DE 69407527 D DE 69407527 T EP 0647145 A ES 2113645 T GR 3025966 T JP 7508678 T NZ 263691 A SG 48702 A	24-01-1995 15-01-1998 27-11-1997 21-11-1994 10-11-1994 05-02-1998 16-07-1998 12-04-1995 01-05-1998 30-04-1998 28-09-1995 26-11-1996 18-05-1998
WO 9702056	A	23-01-1997	SE 504633 C AU 6325996 A CA 2223473 A EP 0841959 A JP 11508469 T SE 9502397 A US 6036858 A	24-03-1997 05-02-1997 23-01-1997 20-05-1998 27-07-1999 04-01-1997 14-03-2000